

Professionall

Solutii profesionale pentru echipamente profesionale



GAS COMPONENTS



ELECTRIC COMPONENTS



WATER TECHNOLOGY



MECHANICAL COMPONENTS



TOOLS

Spare parts suitable for

GRANULDISK



thermostats

control and safety thermostats

EGO

safety thermostats

55.13_series




No.	375977	Ref. No.	14131
description	safety thermostat switch-off temp. 110°C 1-pole probe ø 6mm probe L 129mm capillary pipe 1500mm connection male faston 6.3mm		



No.	375976	Ref. No.	10603 14130
description	safety thermostat switch-off temp. 97°C 1-pole probe ø 6mm probe L 129mm capillary pipe 1470mm connection male faston 6.3mm		

TECASA

control thermostats



No.	375975	Ref. No.	10602 14087
description	thermostat t.max. 120°C temperature range 30-120°C 1-pole 1CO 16A probe ø 6mm probe L 92mm capillary pipe 1850mm capillary pipe isolated 1530mm gland nut shaft ø 6x4.6mm shaft L 16mm shaft position lower rotation 315° 400V no to be sold in France		

control equipment

TELEMECANIQUE (EFA)

XB4 series

rotary switches



No.	347384	Ref. No.	21122
description	rotary selector mounting measurements ø22mm 1NO 0-1 latching		

lamps

indicator lights

indicator lights (complete)

ø22mm



No.	357109	Ref. No.	10270 23709
description	indicator light ø 22mm 250V clear		

solenoïd valves

solenoïd valves (water)

TP







No.	370032	Ref. No.	18191	
description	solenoid valve single straight 24VAC inlet 3/4" outlet 14mm DN10 TP flow regulating valve inlet white			
spare parts for	370032			
	No.	371035	Ref. No.	—
accessories for	370032			
	No.	371220	Ref. No.	—
	reducer TP flow rate 3l/min red tolerance ±15%			
	No.	371221	Ref. No.	—
	reducer TP flow rate 5.5l/min yellow tolerance ±15%			
	No.	371222	Ref. No.	—
	reducer TP flow rate 6l/min grey tolerance ±15%			

Table continues overleaf



accessories for		370032		
No.		371223	Ref. No.	—
	reducer TP flow rate 10l/min white tolerance ±15%			
	reducer TP flow rate 12l/min bronze tolerance ±15%			
	reducer TP flow rate 16l/min light brown tolerance ±15%			
	reducer TP flow rate 20l/min red tolerance ±15%			
	reducer TP flow rate 0.25l/min red tolerance ±25%			
	reducer TP flow rate 0.35l/min violet tolerance ±25%			
	reducer TP flow rate 0.5l/min orange tolerance ±25%			
	reducer TP flow rate 0.8l/min white tolerance ±25%			
	reducer TP flow rate 1l/min light blue tolerance ±25%			
	reducer TP flow rate 1.2l/min brown tolerance ±25%			
	reducer TP flow rate 1.5l/min light brown tolerance ±25%			
	reducer TP flow rate 2.5l/min yellow tolerance ±25%			
	reducer TP flow rate 3.4l/min dark green tolerance ±25%			
	reducer TP flow rate 5l/min black tolerance ±25%			
	reducer TP flow rate 8l/min blue tolerance ±20%			

metal

ASCO

3-way



1

No.	370681	Ref. No.	10540 10540-01 21252
description	solenoid valve brass 3-ways 24VAC connection John Guest 6mm NC DN 1.6mm p max 8.5bar 50/60Hz		



1

No.	370680	Ref. No.	10539 21251
description	solenoid valve brass 3-ways 24VAC connection John Guest 6mm NO DN 1.6mm p max 8.5bar 50/60Hz		

electrodes



1

No.	403322	Ref. No.	10287 10513 10529 22758
description	level electrode 3/8" total length 75mm probe L 46mm insulated probe length 46mm connection M4 thread 3/8"		



equipment-specific units

for dishwashers

miscellaneous



1

No.	692231	Ref. No.	10334
description	bush H 30mm D1 ø 30mm D2 ø 34.5mm ID ø 25.5mm		

gaskets

special gaskets

miscellaneous



1

No.	901527	Ref. No.	18070
description	gasket L 950mm W 135mm Qty 1m thickness 3mm hole distance 93mm		